

REVISITING FOREST ROAD RETIREMENT

Randy Kolka and Mathew Smidt

INTRODUCTION

Determining the sources of nonpoint source pollution in a watershed is difficult, although the largest source of sediment in forested systems is from skid trails, haul roads, and landings associated with forest harvesting (Ketcheson *et al.*, 1999; Swift, 1988). The transport of sediment to streams and subsequent sedimentation leads to the loss of stream habitat and changes in stream hydrology (NCASI, 1999a; 1999b). Forest road position in the landscape, the soil type and geology present, and method of retirement ultimately determines the amount of sediment flux to the stream (Ketcheson *et al.*, 1999; Swift, 1988).

Over the years the use of best management practices (BMPs) for forest road construction and maintenance has

improved water quality. While BMPs have been designed for, and proven to be effective at reducing erosion caused by logging, elevated nonpoint source pollution continues to occur after harvest because of the severe soil disturbance necessary to construct roads (Arthur et al., 1998). The extent of the soil disturbance varies because of topography, seasons, construction methods and harvesting techniques (Kochx, 1991). Soil damage on forest roads is mostly due to compaction and erosion that affects infiltration, surface and subsurface water flow (Wemple et al., 1996). If significant, the resulting erosion can be a major source of sedi-

ment and nutrient losses following the harvest. In eastern Kentucky for example, suspended sediment fluxes for the first two years following harvest were 10-40 times greater in a harvested watershed implemented with BMPs than in an unharvested watershed (Arthur *et al.*, 1998). Nitrogen, phosphorus, and cations followed similar patterns.

Current BMPs for forest roads in many states include seeding, fertilizing, and liming to ensure establishment of the cover crop, diversion of surface water from exposed mineral soil, and restriction of traffic following the harvest (Stringer et al., 1997). With current BMPs, the natural recovery of soil properties, especially bulk density and infiltration, is usually slow and relies on wetting and drying, frost activity, animal activity, and root growth. Subsoil bulk density in forest roads had not recovered to undisturbed levels in 23 years in central Idaho (Froehlich et al., 1985) and 32 years in Oregon (Wert and Thomas, 1981).

The skidding on steep terrain (slopes greater than 30 percent) requires the construction of a relatively dense network of skid trails. In steep terrain 10-25 percent of

the land area can be occupied by bladed skid trails (Stuart and Carr, 1991; Miller and Sirois, 1986; Kochenderfer, 1977). The dense network of skid trails throughout steep regions not only leads to enhanced nonpoint source pollution but also to losses in forest productivity. Tree volume in forest roads has been estimated to be as much as 80 percent less than volume in undisturbed areas (Carr, 1987). Over an entire harvested area growth reductions of 11.8 percent (Wert and Thomas, 1981) and 12 to 15 percent (Smith and Wass, 1979) have been estimated.

Although current BMPs are effective at reducing nonpoint source pollution, few of the current forest road BMPs specifically address the recovery of soil properties, normal hillslope hydrology, and site productivity. We need to develop new techniques to lessen the transport of

sediment and nutrients, minimize the altering of hillslope hydrology, and increase overall forest health and productivity. The USDA Forest Service has recently come under fire to protect roadless areas and to retire or possibly restore roads that receive little use. While numerous methods have been used to retire roads, new technologies have evolved that can potentially ameliorate soil damage and lessen the generation of nonpoint source pollution from forest roads.


Since post-havest treatment of severely disturbed areas such as forest roads and trails is already required by BMPs, it may be possible that an alternative retirement or restoration treatment could partially or completely replace current BMPs.

ALTERNATIVE FOREST ROAD RETIREMENT METHODS

Although not currently part of most state BMPs, others have investigated combinations of practices such as tillage and mulching that are specifically designed for soil and fertility recovery:

- The most effective amelioration techniques for seedling growth included a combination of tillage and fertilization (Reisinger *et al.*, 1988).
- To increase infiltration in areas with deep compaction, subsoil ripping has shown to be effective (Luce, 1997).
- Moll (1996) outlines procedures including different kinds of tillage and partial and complete recontouring for obliteration of forest roads.

The development of Best Management Practices (BMPs) has been heavily influenced by practices that logging contractors could implement to reduce erosion on roads, landings, and skid trails following the timber harvest. The reliance of loggers on logging or road building equipment to implement BMPs has not emphasized retirement practices such as decompaction of soil profiles



Stringer, J., L. Lowe, M.F. Smidt, and C. Perkins, 1997. Field Guide to Best Management Practices for Timber Harvesting in Kentucky. Univ. of Kentucky. Coop. Ext. Serv., Dept. of For. FOR-69.

Stuart, W.B. and J.L. Carr. 1991. Harvesting Impacts on Steep Slopes in Virginia. *In:* Proc. of the 8th Central Hardwood Conference, March 4-6, 1991. Morgantown. West Virginia. USDA Gen. Tech. Rep. NE-148, pp. 67-81.

Swift, L.W. Jr., 1988. Forest Access Roads: Design, Maintenance, and Soil Loss. In: Forest Hydrology and Ecology at Coweeta, W.T. Swank and D.A. Crossley Jr. (Editors). Springer-Verlag, New York, New York, pp. 313-324.

Wemple, B.C. *et al.*, 1996. Channel Network Extentions by Logging Roads in Two Basins, Western Cascades, Oregon. Resour. Bull. 32(6):1195-1207.

Wert, S. and B.R. Thomas, 1981. Effects of Skid Roads on Diameter, Height, and Volume Growth in Douglas Fir. Soil Sci. Soc. Am. J. 45:629-632.

AUTHOR LINK Dr. Randy Kolka

Assistant Professor Department of Forestry

208B Thomas Poe Cooper Building

University of Kentucky Lexington, KY 40546

(859) 257-4208 / Fax: (859) 323-1031

E-Mail rkolk2@pop.uky.edu

Randy Kolka is an Assistant Professor of Forest Hydrology and Watershed Managment in the Department of Forestry at the University of Kentucky. Dr. Kolka received his undergraduate degree in Soil Science from the University of Wisconsin-Stevens Point and his MS and PhD in Soil Science from the University of Minnesota. His primary research interests include Forestry BMP assessment, wetland and riparian hydrology, and carbon, nutrient, mercury and sediment transport. Prior to coming to the University of Kentucky, Dr. Kolka was a Soil Scientist for two years with the USDA Forest Service Southern Research Station studying riparian restoration in bottomland hardwood communities.

Revisiting Forest Road Retirement . . . cont'd.

Mathew Smidt (smidtmf@auburn.edu) is Assistant Extension Specialist and Professor of Forest Operations with the School of Forestry and Wildlife Science at Auburn University. Dr. Smidt recieved a B.S. in Biology form Doane College, M.S. from Duke University, and a Ph.D from the University of Minnesota. As an extension

specialist he has worked with the logging industry to increase the understanding of the costs and benefits of improving logging practices through education and applied research. Prior to moving to Auburn, Dr. Smidt was an extension specialist in timber harvesting at the University of Kentucky.




ATER RESOURCES

May 2001 · Volume 3 · Number

Forest

High Data Rate GOES

The *first* NESDIS-certified High Data Rate GOES transmitter, the SAT HDR GOES, is now available, offering data transmission rates of 300 and 1200 bps between your Campbell Scientific DCP and a GOES satellite.



- NESDIS certified (#1100-001, Nov. 3, 2000) for low and high data rates, including 100, 300, and 1200 bps
- Can be purchased as part of an integrated data collection platform (DCP)
- Automatic GPS correction of clock and oscillator drift
- Transmitter diagnostics and status information can be sampled by the datalogger and transmitted as part of the data stream
- Compatible with most existing Campbell Scientific hydrologic and meteorologic monitoring systems
- Non-volatile setups configured with Windows-based software
- Independent 16 kbyte self-timed and random data buffers
- Low power requirements and an operating temperature range of -40° to +50°C optimize operation in remote locales
- Available on GSA MAS Contract Number GS-25F-6042D

For more info on the SAT HDR GOES call us at (435) 753-2342 or visit our Web site at www.campbellsci.com/hdrgoes.html



WATER RESOURCES

AMERICAN WATER
RESOURCES ASSOCIATION
4 WEST FEDERAL STREET
P.O. Box 1626
MIDDLEBURG, VA 20118-1626
(540) 687-8390 / Fax: (540) 687-8395
E-MAIL: info@awra.org
Homepage: www.awra.org

EDITOR-IN-CHIEF N. EARL SPANGENBERG

College of Natural Resources
University of Wisconsin-Stevens Point
Stevens Point, WI 54481
(715) 346-2372 • Fax: (715) 346-3624
E-Mail: espangen@uwsp.edu

AWRA DIRECTOR OF PUBLICATIONS PRODUCTION CHARLENE E. YOUNG

3077 Leeman Ferry Rd., Suite A3 Huntsville, AL 35801-5690 (256) 650-0701 • Fax: (256) 650-0570 E-Mail: charlenc@awra.org

Water Resources IMPACT is owned and published bi-monthly by the American Water Resources Association, 4 West Federal St., P.O. Box 1626, Middleburg, VA 20118-1626, USA. The yearly subscription rate is \$45.00 domestic and \$55.00 foreign. Foreign Airmail Shipping Option, add \$25.00 to subscription rate. Single copies of IMPACT are available for \$8.00/each. For bulk purchases, contact the AWRA Headquarters office.

IMPACT is a magazine of ideas. Authors, Associate Editors, and the Editor-In-Chief work together to create a publication that will inform and will provoke conversation. The views and conclusions expressed by individual authors and published in Water Resources IMPACT should not be interpreted as necessarily representing the official policies, either expressed or implied, of the American Water Resources Association.

Contact the AWRA HQ Office if you have any questions pertaining to your membership status. For information on advertising rates and deadlines, contact Charlene Young, AWRA Director of Publications Production, at the address given above.

POSTMASTER: Send address changes to Water Resources IMPACT, American Water Resources Association, 4 West Federal St., P.O. Box 1626, Middleburg, VA 20118-1626.

ISSN 1522-3175 VOL. 3 • NO. 3 MAY 2001